

de María

The Cork Experience

CORK STOPPERS NATURAL, FINISHED



One-piece cylinder of natural cork.

Manufactured according to UNE and SYSTECODE PREMIUM and EXCELLENCE standards, and Regulations CE 1935/2004.

Recommended use: *crianza, reserva and signature wines.*

CHARACTERISTICS	PARAMETERS	SPECIFICATIONS
 DIMENSIONS	Length Diameter Ovalisation	38 to 54 mm $\pm$ 0,5 mm 24 to 40 mm $\pm$ 0,4 mm $\leq$ 0,5 mm
 PHYSICAL	Density Humidity Capillarity Extraction force Immediate diametral recovery 5 minute diametral recovery 1 hour diametral recovery	125 – 230 Kg/m ³ 4 – 8% $\leq$ 2,5 mm 15 – 45 daN $\geq$ 88% $\geq$ 93% $\geq$ 95%
 SENSORIAL	Smell	Neutral
 CROMATOGRAPHIC	TCA	According to client's protocol
 CHEMICAL	Residual oxidants	Negative

QUALITIES

We have all the standard qualities available. We can also customize the corks according to the specific quality of each client.

ANALYSIS METHOD

All analyses are carried out according to standards UNE 56921, UNE 56927, UNE 56928, UNE 56929 and UNE 56930, and according to the Systecode control plan (International Code of Good Cork Stopper Manufacturing Practices).

Other parameters or analyses, according to the specifications of each client.

For more information:

info@demariataps.com
www.demariataps.com