

de María

The Cork Experience



CORK STOPPERS

3-PIECE (1+1), FINISHED

Agglomerated cylinder comprising natural cork with a disc of natural cork at each end.

Manufactured according to UNE and SYSTECODE PREMIUM standards, and Regulations CE 1935/2004.

Recommended use: *tables wines, fast-rotation wines and young wines.*

CHARACTERISTICS	PARAMETERS	SPECIFICATIONS
 DIMENSIONS	Length Diameter Thickness of discs	44 to 45 mm $\pm$ 0,5 mm 23,5 mm $\pm$ 0,4 mm $\geq$ 4,0 mm
 PHYSICAL	Density Humidity Capillarity Extraction force Immediate diametral recovery 5 minute diametral recovery 1 hour diametral recovery Deagglomeration	235 - 315 Kg/m ³ 4 - 8% $\leq$ 2,5 mm 15 - 45 daN $\geq$ 87% $\geq$ 91% $\geq$ 93% Non-existent
 SENSORIAL	Smell	Neutral
 CROMATOGRAPHIC	TCA	According to client's protocol
 CHEMICAL	Residual oxidants	Negative

QUALITIES

We have all the standard qualities available. We can also customize the corks according to the specific quality of each client.

ANALYSIS METHOD

All analyses are carried out according to standards UNE 56926, UNE 56927, UNE 56928, UNE 56929 and UNE 56930, and according to the Systecode control plan (International Code of Good Cork Stopper Manufacturing Practices).

Other parameters or analyses, according to the specifications of each client.

For more information:

info@demariataps.com
www.demariataps.com