

de María

The Cork Experience



CORK STOPPERS

AGGLOMERATED WITH CORK DISCS, NATURAL, FINISHED

Cylinder of agglomerated cork with discs of natural cork on each end.

Manufactured according to UNE and SYSTECODE PREMIUM standards, and Regulations CE 1935/2004.
Recommended use: *sparkling wines*.

CHARACTERISTICS	PARAMETERS	SPECIFICATIONS
 DIMENSIONS	Length	48 mm $\pm$ 0,5 mm
	Diameter	30,5 mm or 31 mm $\pm$ 0,3 mm
	Disc thickness (2 discs)	10 – 12 mm
	Bevel height and base	3,5 – 4,5 mm
 PHYSICAL	Mass (48x31mm)	8,4 – 10 g
	Cylinder humidity	4 – 9%
	Disc humidity	4 – 11%
	Torsion	$\geq 7,5$ daN/cm ²
 SENSORIAL	Smell	Neutral
 CROMATOGRAPHIC	TCA	According to client's protocol

QUALITIES

We have all the standard qualities available. We can also customize the corks according to the specific quality of each client.

ANALYSIS METHOD

All analyses are carried out according to standards UNE 56923, UNE 56927, UNE 56928 and UNE 56930, and according to the Systecode control plan (International Code of Good Cork Stopper Manufacturing Practices).

Other parameters or analyses, according to the specifications of each client.

For more information:

info@demariataps.com

www.demariataps.com